

Primer/Filler

2K DTS Sealer

2K direct-to-substrate sealer. Excellent adhesion to metal and to most plastic surfaces. Can be sanded or topcoated wet-on-wet.

Advantages

- › Very good adhesion and corrosion protection
- › Fast drying
- › Can be applied under bodyfiller
- › Can be topcoated with waterborne or solventborne basecoats and single stage topcoats

Article Number

368 4262 (239 g / 8.4 oz.)

Application Notes




Shake can
thoroughly for
1-2 minutes



Apply first coat
adjust variator, perform a
test spray, apply



Allow to flash
5-10 min. between
2-3 coats



Sand wet or dry
(manually)
P400 - P500

Primer/Filler

2K DTS Sealer

2K direct-to-substrate sealer. Excellent adhesion to metal and to most plastic surfaces. Can be sanded or topcoated wet-on-wet.

Advantages

- › Very good adhesion and corrosion protection
- › Fast drying
- › Can be applied under bodyfiller
- › Can be topcoated with waterborne or solventborne basecoats and single stage topcoats

Article Number

368 4262 (239 g / 8.4 oz.)

Application Notes



Shake can
thoroughly for
1-2 minutes



Apply first coat
adjust variator, perform a
test spray, apply



Allow to flash
5-10 min. between
2-3 coats



Sand wet or dry
(manually)
P400 - P500