

# SPRAYMAX 2K EPOXY PRIMER

PRIMER MADE FOR PROFESSIONALS



Universal 2K epoxy primer filler for all problematic surfaces; for example, metal, non-ferrous metal, galvanized sheet steel, or anodized aluminum. Meets OE recommendations for use under seam sealer. Ideal for automotive, industrial and commercial use.

## ADVANTAGES


- Excellent adhesion and corrosion protection properties, even critical surfaces such as aluminium
- Very smooth flow
- Outstanding insulating & sealing properties
- Recoatable with all standard solvent-/ waterborne basecoats or single stage topcoats
- For cleaned and sanded surfaces

## PRODUCT INFORMATIONS

Beige	3680032	(401 g / 14.1 oz.)
Gray	3680033	(382 g / 13.5 oz.)
Black	3680034	(382 g / 13.5 oz.)



APPLICATION  
VIDEO



VARIATOR  
NOZZLE

Peter Kwasny Inc. • Peter Kwasny Spraypaint Canada Inc. • [service@kwasny.us](mailto:service@kwasny.us) • [www.spraymax.com](http://www.spraymax.com)  
For orders: Toll free North America / Sans frais en Amérique du Nord:  
1-844-426-6330 / [order@kwasny.us](mailto:order@kwasny.us)

